



FORGED EYEBOLT

COUPLERS

LONG SERVICE LIFE,
DURABILITY & RELIABILITY

Quality couplers are an essential component for every scaffolding system. They provide essential rigidity, convenience and security when they link together two or a sequence of tubes in virtually any scaffolding configuration. Scafom-rux Couplers are made to quality EN, BS and international standards. Systematic, consistent quality control ensures that all Scafom-rux fittings and accessories deliver their promise of performance.

**SMART
DETAILS
GREAT
SOLUTIONS!**

SCAFOM-RUX **EYEBOLT COUPLERS**



> FORGED EYEBOLT COUPLER

Scafom-rux Eyebolt Couplers are employed to join two or a sequential series scaffold tubes in a diverse range of scaffolding structures. Resilient and robust, Eyebolt Couplers are routinely employed to carry heavy loads or where multiple platforms are required to reach high level project site work stations. The forged eyebolt couplers come in two varieties; a right angle and a swivel coupler.

FAST ACTION, MAINTENANCE FREE THREAD

Both eyebolt couplers are characterized by robust and durable performance benefits. They are equipped with maintenance free bolts, making them less prone to adhesion of dirt and corrosion grime. This important feature significantly lowers assembly/disassembly time, having a direct impact on time-sensitive schedules, labour and overall project costs.

Benefits of Maintenance Free Threads include:

- Maintenance Free Thread equals significant cost reductions
- Ease of assembly and disassembly with fast thread
- Less susceptible to forces of normal wear and tear
- Less prone to adhesion of dirt and corrosive grime
- Greater surface thickness due to increased thread tolerance

> RIGHT ANGLE EYEBOLT COUPLER P55

Right angle couplers are used to connect two scaffolding tubes at 90° angles.


Coupler nut SW22 (WS 7/8")
 Surface treatment: Hot dip galvanised
 Safe working loads for complete connections, in any direction: 6 kN/1348 lbs
 FOS: 4:1

> SWIVEL EYEBOLT COUPLER P54

Swivel couplers are used to connect two scaffolding tubes over a wide range of different work site angles.

Eyebolt Coupler features include:

- Robust design from drop forged steel provides durability, reliability, long service life
- Joins scaffold tubes with outside diameter of 48.3mm
- Hot dip galvanised finish resists corrosion resistance, provides durable functionality
- Compliant with European Quality Standard BS1139/EN74 and other international standards.



Right angle

Eyebolt couplers



Swivel

Eyebolt coupler

Article Nr.	Description	Weight (kg/lbs)
E04AA0459	Right angle SW22	1.6/3.53
E04AA0460	Swivel SW22	1.7/3.75